



# Lanka TorqForce

## Powershift Transmission Fluid

Product Data Sheet



### Customer benefits

- Smooth operation
- Good wear protection
- Long equipment life
- Reliable operation

### Applications

Lanka TorqForce products are suitable for use in power shift transmissions, torque converters, and hydraulic systems.

### Product features:

- **Lanka TorqForce** products are designed to be fit-to-market performance lubricants suitable for use in powershift transmissions, torque converters, and hydraulic systems in Sri Lanka markets. They are manufactured using highly refined base oils and performance additive technologies containing detergents, dispersants, oxidation and corrosion inhibitors, anti-wear agent and a foam suppressant.

The product formulation has long years' experience in these applications in local Sri Lankan operating conditions.

## Typical key properties

LANKA TORQFORCE			
SAE Grade	10W	30	40
Product Code	504302	504303	504304
Pour Point, °C	-30	-18	-17
Density, kg/L at 15°C	0.865	0.908	0.896
Viscosity, Kinematic cSt @ 40°C	37.7	94.8	135.7
cSt @ 100°C	6.3	11.4	14.4
Viscosity Index	116	107	105
Flash Point, °C	220	240	240

Minor variations in product typical test data are to be expected in normal manufacturing.

2106

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

## Performance standards

API SE/CF (SAE 10W, SAE 30, and SAE 40)

### ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit [www.caltex.com](http://www.caltex.com).

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:  
**Chevron Global Lubricants**  
– Asia Pacific